




V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure CookTop V4000 I804



Selected product

- Article no.: 3111200004
- EAN code: 7630029438145
- Type: CTI4T84MMSOLD
- Product category: Hob
- OptiGlass
- Appliance type: Built-in hob
- Standard width: 80 cm
- Front design: BlackDesign
- Frame: DualDesign



Details CookTop V4000 I804

Compliant to regulation

- (EU) Nr. 66/2014
- GB 21456-2008: No

Design

- Type: CTI4T84MMSOLD
- Product category: Hob
- OptiGlass
- Appliance type: Built-in hob
- Standard width: 80 cm
- Front design: BlackDesign
- Frame: DualDesign

Dimensions

- Cut-out height: 8.5 mm
- Cut-out radius: 5 mm
- Appliance height: 51.7 mm
- Appliance width: 761 mm
- Appliance depth: 501 mm
- Appliance corner radius: 2 mm
- Support size width: 750 mm
- Max. support size width: 750 mm
- Support size depth: 490 mm
- Max. support size depth: 490 mm
- Installation height when flush-fitted: 51.7 mm
- Installation height when surface-mounted: 47.7 mm
- Cut-out width when flush-mounted: 767 mm
- Cut-out width when surface-mounted: 750 mm
- Max. cut-out width when surface-mounted: 750 mm
- Cut-out depth when flush-mounted: 507 mm
- Cut-out depth when surface-mounted: 490 mm
- Max. cut-out depth when surface-mounted: 490 mm
- Empty weight: 12 kg
- Cooking zone 1 position: front left
- Cooking zone 1 dimensions: 18 cm
- Cooking zone 2 position: rear left
- Cooking zone 2 dimensions: 21 cm
- Cooking zone 3 position: rear right
- Cooking zone 3 dimensions: 21 cm
- Cooking zone 4 position: front right
- Cooking zone 4 dimensions: 18 cm

Display and operation

- Display: Digital display
- Controls: Multi-Slider/direct selection
- Slider control
- Operating time
- Button sound (on/off)



Energy

- Measurement and Calculation Method: EN60350-2
- Output - standby off: 0.49 W
- Consumption when off: 0 W
- Operating voltage: 220-240 V
- Cooking zone 1 max. power: 3000 W
- Cooking zone 2 max. power: 3700 W
- Cooking zone 3 max. power: 3700 W
- Cooking zone 4 max. power: 3000 W
- Type of connection (1): 380-415 V 2N~
- Type of connection (2): 220-240 V~
- Frequency (1): 50-60 Hz
- Connected loads (1): 7.4 kW
- Connected loads (2): 7.4 kW
- Fuse protection (1): 16 A
- Fuse protection (2): 32 A
- Plug type: Cable
- Cooking zone 1 energy consumption: 640440 J/kg
- Cooking zone 2 energy consumption: 622440 J/kg
- Cooking zone 3 energy consumption: 615240 J/kg
- Cooking zone 4 energy consumption: 645480 J/kg

Hob features

- Induction coil type: MaxiFlex
- OptiGlass
- Hob category: Induction
- Operating time with shut-down function
- Residual heat indicator
- Timer
- Restore function
- Cooking zones: 4
- Power levels: 9
- Heating technology: Induction cooking zones

Functions

- Warming function
- Automatic pan detection
- OptiLink
- Heating function
- GuidedCooking
- Powerplus
- CookingControl
- Safety package
- Pan detection: ab 11cm
- Pause button
- Automatic warm-up function
- Cleaning lock
- Melt function
- Simmer function
- Childproof lock

Additional data

- Feature level: 4

Service and interfaces

- Warranty: 2 years
- Interface: Bluetooth