



V-ZUG Ltd

Industriestrasse 66, P.O.Box, 6302 Zug/Switzerland

Phone +41 58 767 67 67

info@vzug.com, www.vzug.com

Brochure AiroClearWall V4000 Q120



Selected product

- Article no.: 6203100001
- EAN code: 7630029456989
- Type: AW4T-62031
- Product category: Range hood
- Standard width: 120 cm
- Front design: Black mirror glass
- Installation method: Wall hood



Details AiroClearWall V4000 Q120

Compliant to regulation

- (EU) Nr. 65/2014
- (EU) Nr. 66/2014

Design

- Type: AW4T-62031
- Product category: Range hood
- Standard width: 120 cm
- Front design: Black mirror glass
- Installation method: Wall hood

Dimensions

- Device height exhaust air: 855 mm
- Device height exhaust air maximum: 1505 mm
- Front height: 55 mm
- Appliance width: 1198 mm
- Appliance depth: 550 mm
- Max. appliance depth: 550 mm
- Empty weight: 52 kg

Display and operation

- Controls: TouchControl
- Fan power level display
- Lighting: LED
- Number of lights: 2

Energy

- Measurement and Calculation Method: EN61591
- Output - standby off: 0.43 W
- Consumption when off: 0 W
- Energy efficiency class: C
- Annual energy consumption: 159.1 kWh
- Lighting efficiency rating: B
- Fluid dynamic efficiency: 21.6
- Fluid dynamic efficiency rating: C
- Type of connection (1): 220-240 V~
- Nominal lighting output (quantity x W): 1 x 6 W
- Frequency (1): 50-60 Hz
- Connected loads (1): 0.54 kW
- Fuse protection (1): 10 A
- Plug type: BS1363/10A
- Connection cable: 1.5 m

Range hood features

- FlexLED
- Hood design: cubic
- LED candle: LED spot
- SilentPlus
- Activated charcoal filter saturation indicator
- Power levels: 3 + i
- Remote control: Optional, available as accessory
- Grease filter: 4
- ComfortFix
- EcoStandby
- Non-return flap, integrated/attached: Included



Functions

- ComfortFix
- Extracted air
- Activated charcoal filter saturation indicator
- SilentPlus
- TwinBlower
- FlexLED
- Cleaning lock
- Intensive setting
- Automatic after-running time

Additional data

- Light colour in kelvin: 2700 K
- Light colour in kelvin top value: 4000 K
- Exhaust air connection (diameter): 200 mm
- Lighting efficiency: 25.5
- Illumination on cooking surface: 102 lux
- Grease absorption capacity rating: B
- Extracted air output, intensive setting: 1262 m³/h
- Extracted air output, max. setting: 1164 m³/h
- Extracted air output, min. setting: 620 m³/h
- Extracted air noise output, intensive setting: 71 dB(A)
- Extracted air noise level, max. setting: 69 dB(A)
- Extracted air noise output, min. setting: 57 dB(A)
- Connection for fresh air/exhaust air flap
- Motor(s): 2
- Motor output: 530 W
- Feature level: 4

Service and interfaces

- Warranty: 2 + 8 years